

Residential ESS

Lithium-ion Battery CFE-10H





Efficient and flexible

- ✓ Simple buckle fixing minimize the installation time and cost.
- Flexiblet increase voltage capacity without any other equipments



Excellent quality

- 80% of initial capacity after 6000.

 Multiple security protection strategies.



Safe and secure

- ✓ LFP(Lithium ion Phosphate) the highest safety.✓ Up to 8 Series or Parallel.



- Efficient management

 Accurate sampling of voltage and current.

 SOC mathematic more accurate and never jump.

Model	CFE-10H
Total Energy	10.24 kWh
Usable Energy(DC)	8.7 kWh
Max. Discharge Power	10 KW
Rated Capacity	200 Ah
Voltage	48~56 Vd.c
Nominal Voltage	51.2 Vd.c
Operating Condition	Indoor
Charge Operating Temperature	0~45°C
Discharge Operating Temperature	-10~55°C
Dimensions (W*D*H)	700*500*235 mm
Weight	87±1kg
IP Rating	IP 20
Protective Class	I
Parallel or Series Support(Maximum)	8 Parallel or Series
Relative Humidity (RH)	0~95% (No condensed water)
Cooling Type	Ambient cooling
Case Material	Metal
Color	White
Installation	Wall Mounting
Warranty	5 Years
Communication	CAN/RS485
Protection Mode	Triple Hardware Protection
Battery Protection	Over-Current/ Over-Voltage/ Short Circuit/ Under-Voltage/ Over-Temperature
Safety Certificate	UN3480, CE

^[1] Test conditions: 0.2C Charging/Discharging, @25°C, 80% Dod