

Residential ESS

Lithium-ion Battery CFE-5100S



Efficient and flexible

Simple buckle fixing minimize the installation time and cost.
Flexible increase voltage capacity without any other equipments or settings.



Excellent quality

80% of initial capacity after 6000.
Integrated WiFi Modem OTA online upgrade convenient after-sales service



Safe and secure

LFP(Lithium ion Phosphate) the highest safety.
Up to 8 Series or Parallel.



Efficient management

Accurate sampling of voltage and current .
SOC mathematic more accurate and never jump.

Model	CFE-5100S
Total Energy	5.12 kWh
Usable Energy(DC)	4.6 kWh
Max. Discharge Power	5.0 KW
Rated Capacity	100 Ah
Voltage	48~56 Vd.c
Nominal Voltage	51.2 Vd.c
Operating Condition	Indoor
Charge Operating Temperature	0~45°C
Discharge Operating Temperature	-10~55°C
Dimensions (W*D*H)	442*500*133 mm
Weight	42±0.5 kg
IP Rating	IP 20
Protective Class	I
Parallel or Series Support	8 Parallel or Series
Relative Humidity (RH)	0~95% (No condensed water)
Cooling Type	Ambient cooling
Case Material	Metal
Color	White
Installation	Cabinet, Wall Mounting, Ground Installation
Warranty	10 Years
Communication	CAN/RS485
Protection Mode	Triple Hardware Protection
Battery Protection	Over-Current/ Over-Voltage/ Short Circuit/ Under-Voltage/ Over Temperature
Safety Certificate	CE & TUV (IEC 62619, IEC 62040) UL1973 UN3480

CF Energy Co., Ltd.

CFE has offices & warehouses in the following regions where you can get in touch with us:-

Europe: Vienna (Austria) , Budapest (Hungary) Africa: Johannesburg (South Africa)

Asia: Xi'an, Shenzhen, Tianjin, Hong Kong (China) , and Yangon (Myanmar)

Tel: (+86) 029 38367888 Web: www.cfess.cn E-mail: cfenergy@cfess.cn